



SPECIFICATIONS			
Hand Truck Capacity	500 lbs.		
Lifting capacity (keg nose)	200 lbs.		
Lifting speed (lifting 200lbs.)	Up to 4"/second		
Overall height	58"		
Overall width	20"		
Overall depth	27"		
Maximum lifting nose height	40"		
Minimum lifting nose height	1"		
Weight	73 lbs.		
Battery	19.2V/5Ah		
Charger (input/output)	AC110-240V, 50/60Hz, 1.5A max./DC 21.9V, 3.0A		
Battery Capacity/Cycles (lifting 200 lbs.)	90 - 100		

Ships parcel. Some assembly required.

Patent - www.magliner.com/patents

REDUCE INJURIES, IMPROVE PRODUCTIVITY.

- Never manually lift heavy items again!
- Lift up to 200 lbs. up to 40" high ideal for stacking kegs, lifting merchandise and other heavy items, loading vehicles and so much more
- Move up to 500 pounds when used as a traditional hand truck
- Minimizes bending, stretching and lifting
- Electric screw drive lift system provides smooth, quiet operation
- Small footprint allows for easy operation in tight spaces coolers, behind bar, narrow aisles, and small work areas
- Choose from multiple handle, wheel and lifting nose options
- Lifting noses can be removed or changed with a standard Phillips screwdriver
- Internal lithium battery will lift over 90 kegs on a single charge; battery can be partially recharged in a matter of minutes and fully recharged in 3 hours



Battery level indicator



Simple, variable-speed lifting and lowering operation



Integrated kick bar assists with breaking back loads



Optional keg stabilizers eliminate the need for straps when transporting one or two kegs



Stair climbers assist with transporting loads up and down stairs

DESIGN YOUR OWN POWERED LIFTING HAND TRUCK

Handles

HORIZONTAL LOOP



301000 11 1.0 Standard loop.



P/N M/N WT.(LBS., 301008 19 1.5 Standard loop with vinyl sleeve.



301001 24 Horizontal loop handle with straight top.



301188 28 1.5 Horizontal loop handle with straight top and foam sleeve.

SINGLE GRIP WT.(LBS.) 301004 17 2.0

Welded pistol grip.



Welded double grip.

Wheels

MICROCELLULAR



1010 10 Puncture resistant, non-marking tire on one-piece steel hub with





Puncture resistant, non-marking microcellular tire on one-piece high-density, interlocking polyethylene hub with semi-precision bearings.



Puncture resistant, non-marking microcellular tire on one-piece high-density, interlocking polyethylene hub with semi-precision bearings.



Puncture resistant, non-marking microcellular tire on one-piece high-density, interlocking polyethylene hub with semi-precision bearings.



4-ply tube-type tire with three-piece off-set hub and semi-precision bearings.

Lifting Noses

EXTRUDED NOSES



P/N	W"	D"	WT.(LBS.)
521725	17	15	11

Designed to lift and cradle a 1/2 barrel keg or other cylindrical items.

Lifting capacity: 200 lbs.



P/N	W"	D"	WT.(LBS.)
521730	16	12	9

Designed to lift stackable items like cases or boxes.

Lifting capacity: 125 lbs.

Accessories



Designed to cradle upper portion of keg during transport.



magliner.com

- 1205 West Cedar Street | Standish, MI 48658
- **1.800.MAGLINE** (624.5463) (989) 512.1000 (Outside U.S. & Canada)
- ₱ Fax: (989) 803.5941